



40V PNP MEDIUM POWER TRANSISTOR IN SOT23

Features


- BV_{CEO} > -40V
- I_C = -1A High Continuous Current
- I_{CM} = -2A Peak Pulse Current
- Low Saturation Voltage V_{CE(sat)} < -500mV @ -1A
- R_{sat} = 350mΩ for a Low Equivalent On-Resistance
- Complementary NPN Type: FMMT491A
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please <u>contact us</u> or your local Diodes representative. <u>https://www.diodes.com/quality/product-definitions/</u>

Mechanical Data

- Package: SOT23
- Package Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 ⁽³⁾
- Weight: 0.008 grams (Approximate)

Application

- Power MOSFET gate driving
- Low loss power switching



Pin-Out

Ordering Information (Note 4)

Orderable Part Number	Deekere	Morking	Reel Size	Tape Width	Packing	
Orderable Part Number	Package	Marking	(inches)	(mm)	Qty.	Carrier
FMMT591ATA	SOT23 (Type DN)	91A	7	8	3,000	Reel
FMMT591ATC	SOT23 (Type DN)	91A	7	8	10,000	Reel

Notes: 1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.


2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.

3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information

SOT23 (Type DN)



91A = Product Type Marking Code



Absolute Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	Vсво	-40	V
Collector-Emitter Voltage	V _{CEO}	-40	V
Emitter-Base Voltage	VEBO	-7	V
Continuous Collector Current	lc	-1	A
Peak Pulse Current	Ісм	-2	A
Base Current	lв	-200	mA
Peak Base Current	I _{BM}	-1	A

Thermal Characteristics (@TA = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Power Dissipation	(Note 5)	PD	500	mW
Thermal Resistance, Junction to Ambient	(Note 5)	Reja	250	°C/W
Thermal Resistance, Junction to Case	(Note 5)	Rejc	66	°C/W
Thermal Resistance, Junction to Lead	(Note 6)	R _{0JL}	197	°C/W
Operating and Storage Temperature Range		TJ, TSTG	-55 to +150	°C

ESD Ratings (Note 7)

Characteristic	Symbol	Value	Unit	JEDEC Class
Electrostatic Discharge - Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge - Machine Model	ESD MM	400	V	С

Notes: 5. For a device mounted with the collector lead on 15mm × 15mm 1oz copper that is on a single-sided 1.6mm FR-4 PCB; device is measured under still air for a definition mean of the condition of the conditions while the perturbative conditions while the perturbative of a steady-state.
Thermal resistance from junction to solder-point (at the end of the collector lead).
Refer to JEDEC specification JESD22-A114 and JESD22-A115.



Thermal Characteristics and Derating Information






Fig.1 Transient Thermal Impedance








Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Charaot	Symbol	Min	Typ	Max	Unit	Test Condition	
Characteristic			-40	Тур	IVIAX	V	
Collector-Base Breakdown Voltage Collector-Emitter Breakdown Voltage (Note 8)		BVсво				V	$I_{C} = -100\mu A$
	0 (/	BVCEO	-40				$I_{C} = -10 \text{mA}$
Emitter-Base Breakdowr	n Voltage	BVEBO	-7			V	I _E = -100μA
Collector Cutoff Current		I _{CBO}	_	—	-100	nA	$V_{CB} = -30V$
Collector-Emitter Cutoff	Current	ICES		—	-100	nA	$V_{CES} = -30V$
Emitter Cutoff Current		IEBO	_	—	-100	nA	V _{EB} = -5.6V
					-200		Ic = -100mA, I _B = -1mA
Collector-Emitter Saturat	tion Voltage (Note 8)	VCE(sat)	—	_	-350	mV	Ic = -500mA, I _B = -20mA
					-500		I _C = -1A, I _B = -100mA
Base-Emitter Saturation Voltage (Note 8)		VBE(sat)	_	_	-1.1	V	Ic = -1A, I _B = -100mA
Base-Emitter Turn-On V	oltage (Note 8)	VBE(on)	_	—	-1.0	V	Ic = -1A, Vce = -5V
			300			$I_{C} = -1mA$, $V_{CE} = -5V$	
			300		800		Ic = -100mA, Vce = -5V
Static Forward Current T	ransfer Ratio (Note 8)	h _{FE}	250	_	_	_	$I_{C} = -500 \text{mA}, V_{CE} = -5 \text{V}$
	, , , , , , , , , , , , , , , , , , ,		160		_		$I_{C} = -1A, V_{CE} = -5V$
			30		—		$I_{C} = -2A, V_{CE} = -5V$
			450			N411-	$V_{CE} = -10V, I_{C} = -50mA,$
Transition Frequency		ft	150	_	_	MHz	f = 100MHz
Output Capacitance		Cobo	_		10	pF	V _{CB} = -10V, f = 1MHz
	Delay Time	td	_	34.9	_		
Outitation Times	Rise Time	tr	_	19.2	_	nc	Vcc = -10V, Ic = -500mA,
Switching Time	Storage Time	ts	_	249	_		$I_{B1} = -I_{B2} = -25mA$
	Fall Time	tf		62			

Note: 8. Measured under pulsed conditions. Pulse width \leq 300µs. Duty cycle \leq 2%.




Typical Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)





Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.




SOT23 Type DN				
Dim	Min	Max	Тур	
Α	0.89	1.12	1.00	
A1	0.01	0.10	0.05	
b	0.30	0.51	0.45	
c	0.08	0.20	0.10	
D	2.80	3.04	3.00	
Е	2.10	2.64	2.42	
E1	1.20	1.40	1.37	
е	0.95 REF			
e1	1.90 REF			
L	0.25	0.60	0.30	
L1	0.45	0.62	0.54	
All Dimensions in mm				

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT23 (Type DN)



Dimensions	Value (in mm)
С	2.0
Х	0.8
X1	1.35
Y	0.9
Y1	2.9



IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

Diodes' products provided subiect Diodes' Standard and Conditions of 5 are to Terms Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries. All other trademarks are the property of their respective owners. © 2025 Diodes Incorporated. All Rights Reserved.

www.diodes.com