




TERMINAL STRIPS (STANDARD & MINIATURE)

Tin plated lugs and brackets. Bakelite XP .062 (1.57) thick. In addition to the strips shown, we manufacture many other varieties in any configuration and materials required. Send samples or sketch for prompt quotation.



| STANDARD CAT. NO. | FIG. NO. | MINIATURE CAT. NO. |
|-------------------|----------|--------------------|
| 800 | 1 | 837 |
| 801 | 2 | 838 |
| 802 | 3 | 839 |
| 803 | 4 | 840 |
| 804 | 5 | 841 |
| 805 | 6 | 842 |
| 806 | 7 | 843 |
| 807 | 8 | 844 |
| 808 | 9 | 845 |
| 809 | 10 | 846 |
| 810 | 11 | 847 |
| 811 | 12 | 848 |
| 812 | 13 | 849 |
| 813 | 14 | 850 |
| 814 | 15 | 851 |
| 815 | 16 | 852 |
| 816 | 17 | 853 |
| 817 | 18 | 854 |
| 818 | 19 | 855 |
| 819 | 20 | 856 |
| 820 | 21 | 857 |
| 821 | 22 | 858 |
| 822 | 23 | 859 |
| 823 | 24 | 860 |
| 824 | 25 | 861 |
| 825 | 26 | 862 |
| 826 | 27 | 863 |
| 827 | 28 | 864 |
| 828 | 29 | 865 |
| 829 | 30 | 866 |
| 830 | 31 | 867 |
| 831 | 32 | 868 |
| 832 | 33 | — |
| 833 | 34 | — |
| 834 | 35 | — |
| 835 | 36 | — |
| 836 | 37 | — |


BINDING POST STRIPS

FIBERGLASS: Reinforced Polyester NEMA Graded GPO-3 rated for 300°F. (155°C).

GEE: Glass, Epoxy, MIL-I-24768/27 Type G-10. Temp. 300°F. (155°C).

PBE: Paper base electrical, FED. LP-513 Type XP natural, Temp 250°F. max. (121°C).

STANDARD





| XP PHENOLIC CAT. NO. | GLASS EPOXY CAT. NO. | FIBER-GLASS CAT. NO. | L LENGTH | A MTG. CENTERS | NO. OF TERM |
|----------------------|----------------------|----------------------|---------------|----------------|-------------|
| 4187 | 4177 | 4167 | 1.250 (31.8) | .875 (22.2) | 1 |
| 4188 | 4178 | 4168 | 1.687 (42.8) | 1.312 (33.3) | 2 |
| 4189 | 4179 | 4169 | 2.125 (54.0) | 1.750 (44.5) | 3 |
| 4190 | 4180 | 4170 | 2.562 (65.1) | 2.187 (55.5) | 4 |
| 4191 | 4181 | 4171 | 3.000 (76.2) | 2.625 (66.7) | 5 |
| 4192 | 4182 | 4172 | 3.437 (87.3) | 3.062 (77.8) | 6 |
| 4193 | 4183 | 4173 | 3.875 (98.4) | 3.500 (88.9) | 7 |
| 4194 | 4184 | 4174 | 4.312 (109.5) | 3.937 (100.0) | 8 |
| 4195 | 4185 | 4175 | 4.750 (120.7) | 4.375 (111.1) | 9 |
| 4196 | 4186 | 4176 | 5.187 (131.7) | 4.812 (122.2) | 10 |

Terminals supplied on these strips



CAT. NO. 1248

HEAVY DUTY



| GLASS EPOXY CAT. NO. | FIBER-GLASS CAT. NO. | L LENGTH | A MTG. CENTERS | NO. OF TERM |
|----------------------|----------------------|--------------|----------------|-------------|
| 4147 | 4157 | 1.50 (38.1) | 1.00 (25.4) | 1 |
| 4148 | 4158 | 2.00 (50.8) | 1.50 (38.1) | 2 |
| 4149 | 4159 | 2.50 (63.5) | 2.00 (50.8) | 3 |
| 4150 | 4160 | 3.00 (76.2) | 2.50 (63.5) | 4 |
| 4151 | 4161 | 3.50 (88.9) | 3.00 (76.2) | 5 |
| 4152 | 4162 | 4.00 (101.6) | 3.50 (88.9) | 6 |
| 4153 | 4163 | 4.50 (114.3) | 4.00 (101.6) | 7 |
| 4154 | 4164 | 5.00 (127.0) | 4.50 (114.3) | 8 |
| 4155 | 4165 | 5.50 (139.7) | 5.00 (127.0) | 9 |
| 4156 | 4166 | 6.00 (152.4) | 5.50 (139.7) | 10 |

Terminals supplied on these strips



CAT. NO. 1209