

## SMALL SIGNAL NPN TRANSISTOR



### PRELIMINARY DATA

| Ordering Code | Marking | Package / Shipment |
|---------------|---------|--------------------|
| 2N3904        | 2N3904  | TO-92 / Bulk       |
| 2N3904-AP     | 2N3904  | TO-92 / Ammopack   |

- SILICON EPITAXIAL PLANAR NPN TRANSISTOR
- TO-92 PACKAGE SUITABLE FOR THROUGH-HOLE PCB ASSEMBLY
- THE PNP COMPLEMENTARY TYPE IS 2N3906

### APPLICATIONS

- WELL SUITABLE FOR TV AND HOME APPLIANCE EQUIPMENT
- SMALL LOAD SWITCH TRANSISTOR WITH HIGH GAIN AND LOW SATURATION VOLTAGE



### ABSOLUTE MAXIMUM RATINGS

| Symbol    | Parameter   | Value      | Unit             |
|-----------|---|------------|------------------|
| $V_{CBO}$ | Collector-Base Voltage ( $I_E = 0$ )                  | 60         | V                |
| $V_{CEO}$ | Collector-Emitter Voltage ( $I_B = 0$ )               | 40         | V                |
| $V_{EBO}$ | Emitter-Base Voltage ( $I_C = 0$ )                    | 6          | V                |
| $I_C$     | Collector Current                                     | 200        | mA               |
| $P_{tot}$ | Total Dissipation at $T_C = 25\text{ }^\circ\text{C}$ | 625        | mW               |
| $T_{stg}$ | Storage Temperature                                   | -65 to 150 | $^\circ\text{C}$ |
| $T_j$     | Max. Operating Junction Temperature                   | 150        | $^\circ\text{C}$ |

## THERMAL DATA

|                         |                                     |     |      |      |
|-------------------------|-------------------------------------|-----|------|------|
| R <sub>thj-amb</sub> •  | Thermal Resistance Junction-Ambient | Max | 200  | °C/W |
| R <sub>thj-case</sub> • | Thermal Resistance Junction-Case    | Max | 83.3 | °C/W |


ELECTRICAL CHARACTERISTICS (T<sub>case</sub> = 25 °C unless otherwise specified)

| Symbol                | Parameter  | Test Conditions  | Min.                        | Typ. | Max.         | Unit   |
|-----------------------|--|--|-----------------------------|------|--------------|--------|
| I <sub>CEX</sub>      | Collector Cut-off Current (V <sub>BE</sub> = -3 V)       | V <sub>CE</sub> = 30 V   |                             |      | 50           | nA     |
| I <sub>BEX</sub>      | Base Cut-off Current (V <sub>BE</sub> = -3 V)            | V <sub>CE</sub> = 30 V   |                             |      | 50           | nA     |
| V <sub>(BR)CEO*</sub> | Collector-Emitter Breakdown Voltage (I <sub>B</sub> = 0) | I <sub>C</sub> = 1 mA  | 40                          |      |              | V      |
| V <sub>(BR)CBO</sub>  | Collector-Base Breakdown Voltage (I <sub>E</sub> = 0)    | I <sub>C</sub> = 10 μA   | 60                          |      |              | V      |
| V <sub>(BR)EBO</sub>  | Emitter-Base Breakdown Voltage (I <sub>C</sub> = 0)      | I <sub>E</sub> = 10 μA   | 6                           |      |              | V      |
| V <sub>CE(sat)*</sub> | Collector-Emitter Saturation Voltage                     | I <sub>C</sub> = 10 mA    I <sub>B</sub> = 1 mA<br>I <sub>C</sub> = 50 mA    I <sub>B</sub> = 5 mA   |                             |      | 0.2<br>0.2   | V<br>V |
| V <sub>BE(sat)*</sub> | Base-Emitter Saturation Voltage                          | I <sub>C</sub> = 10 mA    I <sub>B</sub> = 1 mA<br>I <sub>C</sub> = 50 mA    I <sub>B</sub> = 5 mA   | 0.65                        |      | 0.85<br>0.95 | V<br>V |
| h <sub>FE*</sub>      | DC Current Gain  | I <sub>C</sub> = 0.1 mA    V <sub>CE</sub> = 1 V<br>I <sub>C</sub> = 1 mA       V <sub>CE</sub> = 1 V<br>I <sub>C</sub> = 10 mA      V <sub>CE</sub> = 1 V<br>I <sub>C</sub> = 50 mA      V <sub>CE</sub> = 1 V<br>I <sub>C</sub> = 100 mA     V <sub>CE</sub> = 1 V | 60<br>80<br>100<br>60<br>30 |      | 300          |        |
| f <sub>T</sub>        | Transition Frequency                                     | I <sub>C</sub> = 10 mA    V <sub>CE</sub> = 20 V    f = 100 MHz  | 250                         | 270  |              | MHz    |
| C <sub>CB0</sub>      | Collector-Base Capacitance                               | I <sub>E</sub> = 0    V <sub>CB</sub> = 10 V    f = 1 MHz  |                             | 4    |              | pF     |
| C <sub>EBO</sub>      | Emitter-Base Capacitance                                 | I <sub>C</sub> = 0    V <sub>EB</sub> = 0.5 V    f = 1 MHz   |                             | 18   |              | pF     |
| NF                    | Noise Figure   | V <sub>CE</sub> = 5 V    I <sub>C</sub> = 0.1 mA    f = 10 Hz<br>to 15.7 KHz    R <sub>G</sub> = 1 KΩ  |                             | 5    |              | dB     |
| t <sub>d</sub>        | Delay Time   | I <sub>C</sub> = 10 mA    I <sub>B</sub> = 1 mA  |                             |      | 35           | ns     |
| t <sub>r</sub>        | Rise Time  | V <sub>CC</sub> = 30 V   |                             |      | 35           | ns     |
| t <sub>s</sub>        | Storage Time   | I <sub>C</sub> = 10 mA    I <sub>B1</sub> = -I <sub>B2</sub> = 1 mA  |                             |      | 200          | ns     |
| t <sub>f</sub>        | Fall Time  | V <sub>CC</sub> = 30 V   |                             |      | 50           | ns     |

\* Pulsed: Pulse duration = 300 μs, duty cycle ≤ 2 %


## TO-92 MECHANICAL DATA

| DIM. | mm       |      |          | inch     |      |          |
|------|----------|------|----------|----------|------|----------|
|      | MIN.     | TYP. | MAX.     | MIN.     | TYP. | MAX.     |
| A    | 4.32     |      | 4.95     | 0.170    |      | 0.195    |
| b    | 0.36     |      | 0.51     | 0.014    |      | 0.020    |
| D    | 4.45     |      | 4.95     | 0.175    |      | 0.194    |
| E    | 3.30     |      | 3.94     | 0.130    |      | 0.155    |
| e    | 2.41     |      | 2.67     | 0.095    |      | 0.105    |
| e1   | 1.14     |      | 1.40     | 0.045    |      | 0.055    |
| L    | 12.70    |      | 15.49    | 0.500    |      | 0.609    |
| R    | 2.16     |      | 2.41     | 0.085    |      | 0.094    |
| S1   | 1.14     |      | 1.52     | 0.045    |      | 0.059    |
| W    | 0.41     |      | 0.56     | 0.016    |      | 0.022    |
| V    | 4 degree |      | 6 degree | 4 degree |      | 6 degree |



**TO-92 AMMOPACK SHIPMENT (Suffix"-AP") MECHANICAL DATA**

| DIM.    | mm    |       |       | inch   |       |       |
|---------|-------|-------|-------|--------|-------|-------|
|         | MIN.  | TYP.  | MAX.  | MIN.   | TYP.  | MAX.  |
| A1      |       |       | 4.80  |        |       | 0.189 |
| T       |       |       | 3.80  |        |       | 0.150 |
| T1      |       |       | 1.60  |        |       | 0.063 |
| T2      |       |       | 2.30  |        |       | 0.091 |
| d       |       |       | 0.48  |        |       | 0.019 |
| P0      | 12.50 | 12.70 | 12.90 | 0.492  | 0.500 | 0.508 |
| P2      | 5.65  | 6.35  | 7.05  | 0.222  | 0.250 | 0.278 |
| F1,F2   | 2.44  | 2.54  | 2.94  | 0.096  | 0.100 | 0.116 |
| delta H | -2.00 |       | 2.00  | -0.079 |       | 0.079 |
| W       | 17.50 | 18.00 | 19.00 | 0.689  | 0.709 | 0.748 |
| W0      | 5.70  | 6.00  | 6.30  | 0.224  | 0.236 | 0.248 |
| W1      | 8.50  | 9.00  | 9.25  | 0.335  | 0.354 | 0.364 |
| W2      |       |       | 0.50  |        |       | 0.020 |
| H       | 18.50 |       | 20.50 | 0.728  |       | 0.807 |
| H0      | 15.50 | 16.00 | 16.50 | 0.610  | 0.630 | 0.650 |
| H1      |       |       | 25.00 |        |       | 0.984 |
| D0      | 3.80  | 4.00  | 4.20  | 0.150  | 0.157 | 0.165 |
| t       |       |       | 0.90  |        |       | 0.035 |
| L       |       |       | 11.00 |        |       | 0.433 |
| I1      | 3.00  |       |       | 0.118  |       |       |
| delta P | -1.00 |       | 1.00  | -0.039 |       | 0.039 |



Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a trademark of STMicroelectronics

© 2003 STMicroelectronics – Printed in Italy – All Rights Reserved

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>