

# PTS830 Series Microminiature SMT Top Actuated



## Features/Benefits

- 3.5 x 2.6 mm footprint
- High number of cycles
- Optional ground pin

## Typical Applications

- Wearable electronics
- Nomad devices
- Remote controls
- Keyless entry system

## Specifications

FUNCTION: momentary action  
 CONTACT ARRANGEMENT: 1 make contact = SPST N.O.  
 TERMINALS: G type for SMT  
 TRAVEL: 0.15 mm ± 0.1 mm

	Operating Force (gf)	Life Cycles	Ground Pin
PTS830 GM140 SMTR LFS	160 ± 50	500,000	No
PTS830 GG140 SMTR LFS	450 ± 80	200,000	No
PTS830 GM140G SMTR LFS	160 ± 50	500,000	Yes
PTS830 GG140G SMTR LFS	450 ± 80	200,000	Yes

## Packaging

Switches in reels of 9,500 pieces  
 Dimensions of reels according to EIA 481B  
 External diameter 330 mm

## Electrical

MAXIMUM VOLTAGE: 12 VDC  
 MAXIMUM CURRENT DC: 50 mA  
 DIELECTRIC STRENGTH: 100 VA C (1mn)  
 CONTACT RESISTANCE: ≤ 100 mΩ  
 INSULATION RESISTANCE: ≥ 100 MΩ  
 BOUNCE TIME: ≤ 10 ms

## Environmental

OPERATING TEMPERATURE: -40°C to 85°C

## Process

SOLDERING: This component is suited to the following methods:  
 Infrared Reflow Soldering in accordance with IEC61760-1


### NOTE:

- Specifications listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.
- The PTS series is not certified for using in Automotive application and no PPAP. However, in the case of some automotive accessories and specific applications for 2 and 3 wheeled vehicles the PTS is widely used and very suitable. Please contact your local C&K representative to discuss your application and the best switch solution.

## How To Order


Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.

For any part number different from those listed above, please consult your local representative.





# PTS830 Series Microminiature SMT Top Actuated





## PTS830 GX 140 SMTR LFS



RECOMMENDED PCB LAYOUT



SCHEMATIC




B  
Tactile Switches




# PTS830 Series Microminiature SMT Top Actuated






PTS830 GX 140 G SMTR LFS




RECOMMENDED PCB LAYOUT




SCHEMATIC



DETAIL C  
SCALE 38



CARRIER TAPE



REEL

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## [C&K Switches:](#)

[PTS830GM140SMTRLFS](#) [PTS830GG140SMTRLFS](#) [PTS830GM140GSMTRLFS](#) [PTS830GG140GSMTRLFS](#)  
[PTS830GG140SMTR LFS](#) [PTS830GM140SMTR LFS](#) [PTS830GM140GSMTR LFS](#) [PTS830GG140GSMTR LFS](#)